

AP00.20-U-0001C **SERVICE SHEET for Flexible Service System (FSS)** 25.9.97

MODEL 170

Passenger Cars Model Year 2003

USA/CANADA:

System is also known as "Active Service System (ASSYST)" in the Workshop Information System (WIS)

Model 170



Cus	stomer:		-	Repair order number:		
Confirm work has been performed by signing below				Type of servi	ce last performed	
Technician:				Ţ	1	_
		De	etermine need for service:	B	Ā	
	Please define type	of service to be perfo	ormed here:			
	Current		odometer reading:		_	
	B-Service last	performed	at mi/km:		_	
	(Enter 0 if B-Service	is performed for firs	t time)			
	Difference		in mi/km:		-	
	NA delicio de la constanta de		Difference < 14,000 mi 22,000 km	Difference ≥ 14,000 22 000 B-5		
Determine "Additional work" needed, if any: 50,000 m (check if applicable)		50,000 mi/8	0,000 km or 4 years	every:	2 years	
		60,000 mi/9	6,000 km or 4 years		Spark plugs	
		60,000 mi/9	6,000 km or 5 years			
		150,000mi/250),000km or 15 years			
i See last pa	age for"Additiona	al work"				

Determining need for A-Service or B-service:

If the distance driven since the last "B-Service" is less (<) than 14,000 miles/22 000 km (as determined from Service Booklet or dealer records), an "A-Service" should be performed.

If the distance driven since the last "B-Service" is greater (≥) than 14,000 miles/22 000 km (as determined from Service Booklet or dealer records), a "B-Service" should be performed.

completed	IX	A-Service		O B-Service	Not O.K.	
	V	Vehicle passenger compartment	V	V	V	
505		venicle passenger compartment				
		Function check				
		Warning/indicator lamps, illumination and interior lighting		\otimes		
		Windshield wipers, windshield washer system	\boxtimes	\otimes		AP82.35-P-8252BA
		Headlamp cleaning system	\boxtimes	\otimes		
		Check seat belts for damage and proper function		\otimes		AP91.40-P-9150Z
		Reset FSS counter in instrument cluster	\boxtimes	\otimes		
		Wheels				
		Check front brake pads for lining thickness (remove 1 front wheel at "A" service)	\boxtimes			AP42.10-P-4251BA
		Check brake pad thickness (front and rear)		\otimes		AP42.10-P-4251BA
		Check condition of brake discs front and rear		\otimes		AP42.10-P-4251BA
		Check tires for damage and condition	\boxtimes	\otimes		AP40.10-P-4051Z
		Measure tread depth, enter in mm		\otimes		AP40.10-P-4051Z
		LF RF LR RR				
		outside				
-		center				
		inside				
		Correct tire inflation pressure	\boxtimes	⊗		
		Vehicle underbody				
complete	ıΣ	A-Service		O B-Service	Not O.K.	
	\downarrow		\downarrow	<u> </u>	↓	
		Visual check for Leakage - Major components Chafe marks, line routing, components. In the event of leakage, determine cause and perform repair via separate work order.		⊗		AP00.20-P-0053BA
		Check condition of front axle ball joints and rubber boots		\otimes		AP33.20-P-3353BA
		Check condition of steering's mechanical components and rubber boots		\otimes		AP46.00-P-4653BA

		matalanan and a same a			 		
		Engine compartment					
		Visually check Leakage - Major components Chafe marks, line routing, components. In the event of leakage, determine cause and perform repair via separate work order.		⊗			AP00.20-P-0053BA
		Engine oil and filter change Engine 111	\boxtimes	\otimes			AP18.00-P-0101AD
		Engine 112					AP18.00-P-0101AE
		Check and correct fluid level					
		Brake system	\boxtimes	\otimes			AP42.10-P-4210Z
		Power steering		\otimes			AP46.00-P-4611BB
		If so equipped:	\boxtimes	\otimes			AP54.10-P-5410A
		Battery, wet cell Check acid level, replenish					
		Additionally, check battery condition using "Midtronics MCR 717" Tester	X	\otimes			SI54.10-P-0003A
		If so equipped: Battery, AGM/VRLA, with black housing Check battery condition using "Midtronics MCR 717" Tester		⊗			SI54.10-P-0003A
	п	Windshield washer	\boxtimes	\otimes		П	AP82.35-P-8210Z
·		Lubricate throttle linkage, check function and condition		\otimes			AP30.10-P-3022ZA
		Check catch, safety catch and hinges on engine hood for proper operation. Replace components with even slightest malfunction.		\otimes			AP88.40-P-8821BA
		Additional Work	**************************************				
	completed \boxtimes	Perform:	yes ↓		Not (Ο.Κ. ↓	
		At approx. every 50,000 mi/80,000 km or 4 years:					
F AP		Check condition of drive shaft flex discs					AP41.10-P-4152Z
₩AP		Retighten bolts for steering box. Observe torque.					AP46.20-P-4671BA
		At approx. every 60,000 mi/96,000 km or 4 years:					
₩AP		Replace air cleaner filter element					

	At approx. every 60,000 mi/96,000 km or 5 years:		
₩AP	Replace fuel filter Engine 111		AP47.20-P-0780DB
	Engine 112		AP47.20-P-0780DC
	Check condition of poly-V-belt		AP13.22-P-1351Z
	Every 2 years		
	Replace dust filter		AP83.00-P-8381G
₩AP	Replace brake fluid		AP42.00-P-4280BA
F AP	Inspect body for paint damage by Service Advisor		AP98.00-P-9850BA
₩AP	Check chassis and supporting body parts: for damage and corrosion by Service Advisor		AP00.20-P-0090BA
	At approx. every 150,000 mi/250,000 km or 15 years		
βFAP	Replace coolant		AP20.00-P-2080DA
	Replace spark plugs		
₩ AP	At approx. every 30,000 mi/50,000 km or 4 years Engine 111 - M.Y. 1998 - 2000		AP15.10-P-1580CA
⊯ AP	At approx. every 100,000 mi/160,000 km or 5 years Engine 111 - As of M.Y. 2001 Engine 112		AP15.10-P-1580A