

AP00.20-U-1208VAD SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 171

AMG models only

Passenger cars Model Year 2008

USA

Model 171	
-----------	--



Customer:		Repair order number:			
First visit	at 1,000 - 3,000 miles	Performed YES NO			
Rear axle differential fluid replacement	during first visit (SLK55 with AMG performance package only)	Performed YES NO			
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated YES NO			
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected YES NO			
Current mileage reading:		Oil grade/viscosity:	_		
Additional notes:			_		
Service work to be performe service advisor:	d as advised by Completion date:	Confirm work has been performed by signing below:			

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2. Perform each service as described.

US Service		first at 10,000 mi or 1 year;	after first every 20,000 mi or 2 years	
1	US Service 2	first at 20,000 mi or 2 years;	after first every 20,000 mi or 2 years Not OK	
↓ ↓	∠ ↓		votok ↓	
600		Interior		
	О	Reset service indicator in instrument cluster		AP00.20-P-0042V
		Function check		
	0	Horn		
	0	Warning/indicator lamps, illumination and interior lighting		AP54.30-P-5452C
	0	Windshield wipers, windshield washer sy- stem, headlamp cleaning system		AP82.30-P-8252V
	0	Check seat belts and buckles for signs of ex- ternal damage and proper function		AP91.40-P-9150V
	0	Check parking brake (function test only)		
E		Wheels, brakes		
	† 0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Inspect tires for damage and splits, measu- re tread depth, record in mm: LF RF LR RR outside		AP40.10-P-4051Z
	-	center		
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR		
		bar/psi: Engine compartment		
		Engine compartment		
	0	Leakage - Major components Check for chafe marks, line routing, dama- ged components in the event of leakage, determine cau- se and perform repair via separate work or- der		AP00.20-P-0053V
	0	Check catch, safety catch and hinges on en- gine hood for proper operation.		AP88.40-P-8851V
	0	Battery, check and correct fluid level		AP54.10-P-5410V
	0	Battery, check battery condition using "Midtronics MCR 717" Tester. Attach Mid- tronics MCR 717 Test Report print out here.		
	0	Check condition of poly-V-belt		
		Check fluid level, correct as required i If there is a loss of fluid, determine cau- se and perform repair via separate work or- der		
	0	Brake system		AP42.10-P-4210V
	0	Power steering		AP46.00-P-4611V
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210N

US Service US Service 1			Not OK	
I ↓	2 ↓		ţ	
	•	Underside of vehicle	v	
τ'τ	0	Leakage - Major components Check for chafe marks, line routing, dama- ged components i In the event of leakage, determine cau- se and perform repair via separate work or- der		AP00.20-P-0053V
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353V
	0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152V
	0	Inspect play of tie rod and and drag link joints, inspect rubber boots		AP46.00-P-4653V
	,	Vehicle front/rear		
	0	Check wiper blade condition		AP82.30-P-8253G
	0	Check and correct headlamp setting		AP82.10-P-8260V
ieo Do	j	Trunk		
	Ο	Check trunk lighting		
Completed			Not OK	
	Ļ		\downarrow	
US Service 3		every 10,000 mi or 1 year:		
	_	Engine compartment		
		Engine - oil and filter change		AP18.00-P-0101VT
US Service 4	_	every 2 years:	_	
		Check bodywork for paint work damage by service advisor		AP98.00-P-9850BA
	_	Underside of vehicle	_	
		Chassis and load-bearing body compo- nents: Check for damage and corrosion by service advisor		AP00.20-P-0090BA
		Engine compartment		
		Replace brake fluid		AP42.00-P-4280V
US Service 5		every 30,000 mi or 2 years:		
		Passenger compartment		
		Replace combination filter		AP83.00-P-8384V
US Service 6		every 40,000 mi:		
		Replace rear axle differential fluid (SLK55 with AMG performance package only)		
US Service 7		not applicable		
US Service 8		every 40,000 mi or 4 years:		
		Engine compartment		
		Replace engine air-cleaner insert		AP09.10-P-0980VT
US Service 9 and 1	10	not applicable		
		••		

Complete	×۲			Not OK ↓	
US Service 11		every 150,000 mi or 15 years:			
		Trunk			
		Replace fuel filter			AP47.20-P-0780Q
US Service 12		every 100,000 mi or 5 years:			
		Engine compartment			
		Replace spark plugs (Engine 113)			AP15.10-P-1580VT
US Service 13		every 150,000 mi or 15 years:			
		Engine compartment			
		Replace coolant			AP20.00-P-2080VT
US Service 14-19)	not applicable			
US Service 20		once at 40,000 mi			
		Underside of vehicle			
		Automatic transmission - oil and filter change			AP27.00-P-2702W
Completed	× ↓	Perform:	Yes ↓	Not OK ↓	
		Vehicle over 150,000 mi:			
		Check if all fluid levels and changes are up- dated			
AP		Transmission			
AP		Rear axle			
		Check if air, fuel, ventilation filters are up- dated			
₩AP		Engine air filter			
₩ A P		Fuel filter			
₩AP		Combination filter			
		Check integrity of engine, mechanical co- monents			
₩ AP		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
₩ A P		Perform leak down test (hot and cold)			AP00.20-P-0053V
₩ AP		Check spark plugs			
₩ AP		Exhaust system hangers and leaks			
		Check damaged / worn drivetrain parts			
₩ AP		Front wheel bearing play			
₩ AP		Rear wheel bearing play			
₩AP		Axle joint play			
₩ AP		Driveshaft flexible discs			
₩ AP		Tie rod and drag link joints			