


AP00.20-U-1208FD SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 28.3.07

MODEL 204 except AMG models

## Passenger cars Model Year 2008



Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non-staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading: Oil grade/viscosity:				
Service work to be performed as advised by completion date: service advisor:		Confirm work has been performed by signing below:		

i

Service 4-20 apply to "Additional work" items only.

Vehicle determines need for Service 3 (Engine oil and filter change) as well as Service A and Service B.

Perform each service as described.

Service A		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
A	Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
↓	B ↓		Not OK ↓	
60		Interior		
	0	Reset service indicator in instrument cluster		
		Comfort multifunctional steering wheel (12 buttons)		AP00.20-P-0042CV
	0	Replace combination filter		AP83.00-P-8384CW
	$\circ$	Function test Indicator lamps in instrument cluster,	П	AP54.30-P-5452C
	O	interior illumination	Ц	Ar 34.30-r -3432C
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252CW
	0	Check parking brake (function test only)		
		Wheels, brakes		
	0	Inspect tires for damage and splits, measure tread depth, enter in mm:  LF RF LR RR		AP40.10-P-4051CW
		outside		
	0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi.  LF RF LR RR		
		bar/psi:		
		Underside of vehicle		
	0	<b>Leakage - Major components</b> Check for chafe marks, line routing, dama-		AP00.20-P-0053CW
		ged components  i In the event of leakage, determine cause and perform repair via separate work order		
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353CW
	0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152CW
	0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653CW
160		Vehicle front/rear		
	0	Check and correct headlamp setting		AP82.10-P-8260CW
	0	Check wiper blade condition		AP82.30-P-8253CW
		Trunk		
	0	Correct inflation pressure of spare tire and enter in bar or psi. bar/psi:		
	0	Check trunk lighting		

Service	Service		Not OK	
<b>A</b> ↓	<b>B</b> ↓		<b>↓</b>	
	<del>\</del>	Engine compartment	<u> </u>	
	0	Leakage - Major components Check for chafe marks, line routing, damaged components  i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053CW
	0	Check condition of poly-V-belt		
	0	Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		
		Check fluid level, correct as required  ilf there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Brake system		AP42.10-P-4210CW
	0	Power steering		AP46.00-P-4611CW
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210CW
		Additional Work		
Comp	oleted ⊠ ↓		Not OK ↓	
US Servic	:e 3	every 13,000 mi or 1 year:		
		Engine compartment		
		Engine - oil and filter change		AP18.00-P-0101CWZ
US Servic	:e 4	every 2 years:		
		Check bodywork for paint work damage by service advisor		AP98.00-P-9850CW
		Underside of vehicle  Chassis and load-bearing body components: Check for damage and corrosion by service advisor		AP00.20-P-0090CW
		Engine compartment		
		Replace brake fluid		AP42.00-P-4280CW
US Service	5 -7	not applicable		
US Servic	e <b>8</b>	every 52,000 mi or 4 years:		
		Engine compartment		
		Replace engine air-cleaner insert		AP09.10-P-0980CWZ
US Servic	:e 9	not applicable		
US Service	e 10	every 39,000 mi or 3 years:		
	_	Passenger compartment		
		Panoramic sliding roof - clean and lubricate quide mechanism		AP77.20-P-7732CW

Completed	IX			Not OK	
	<u> </u>			<u>_</u>	
US Service 11		every 143,000 mi or 15 years:			
	_	Passenger compartment			
		Replace fuel filter			AP47.20-P-0780CWZ
US Service 12 Engine 272		every 91,000 mi or 5 years: Engine compartment			
,		Replace spark plugs			AP15.10-P-1580CWZ
US Service 13		every 143,000 mi or 15 years:			
		Engine compartment			
		Replace coolant			AP20.00-P-2080CW
US Service 14 - 19	)	not applicable			
US Service 20		once at 39,000 mi: Underside of vehicle			
		Automatic transmission - oil and filter change			AP27.00-P-2702W
Completed	X	Perform:	Yes	Not OK	
	$\downarrow$		<b>↓</b>	<b>↓</b>	
		Vehicle over 143,000 mi:			
		Check if all fluid levels and changes are updated			
₩AP		Transmission			
₩AP		Rear axle			
⊫FAP		Front axle (if applicable)			
FFAP		Transfer case (if applicable)			
		Check if air, fuel, ventilation filters are updated			
FAP		Engine air filter			
₩ÃΡ		Fuel filter			
₩ÃΡ		Combination filter			
		Check integrity of engine, mechanical comonents			
FAP		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
FFAP		Perform leak down test (hot and cold)			AP00.20-P-0053CW
FAP		Check spark plugs			
₩ÃΡ		Exhaust system hangers and leaks			
		Check damaged / worn drivetrain parts			
FAP		Front wheel bearing play			
₩AP		Rear wheel bearing play			
<b>⊯</b> AP		Axle joint play			
<b>⊯</b> AP		Driveshaft flexible discs			
₩AP		Tie rod and drag link joints			