

AP00.20-U-1208BA

Service Sheet for Mercedes-Benz Maintenance System (USA)

15.03.04

MODEL 209 AMG models only

Passenger Cars Model Year 2005

USA



Customer:			Repair order number:				
First visit	at 1,000 - 3,000 miles		Performed	YES	NO		
Tire Rotation (non-staggered width wheel setup only)		Performed in accordance with the tire nanufacturer's recommended intervals		YES	NO		
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for dama tire inflation pressure	ge and correct	Tires inspected	YES	NO		
Current mileage reading: _		(Dil grade/viscosity:				
Additional notes:							
Service work to be perform service advisor:	ed as advised by	Completion da		onfirm work has bee gning below:	en performed by		
1st A service at 10,000) miles or 1 year, then	every 20,000 mi	iles or 2 years				
1st B service at 20,00	0 miles or 2 years, the	n every 20,000 r	niles or 2 years				
Determine "Additional	work" needed, if any.	Refer to "Additi	onal Work" sec	tion			
(check if applicable)	40.000			2			
once at first service at:	10,000 mi or 1 year		every:	2 years			
at approx. every:	50,000 mi or 4 years			5 years			
	60,000 mi or 4 years			Spark plugs			
	60,000 mi or 5 years		at approx.:	150,000 mi			
	150,000 mi or 15 years						
i See last page for "Add Additional flat rates ap	litional work". oply for procedures marked	l with 🎼 AP					
74-209AMG-05A (03/04) er Workshop Services MBUSA.com		Mercedes-Benz USA, LLC		Reproduction or translation in without written authorization fr 1-1800-FOR-MERCedes			

1

completed	A-Service	□↓	O B-Service ↓	Not O.⊮ ↓	ς.
	Interior				
	Reset maintenance counter in instrument cluster	X	\otimes		
	Replace dust filter		\otimes		AP83.00-P-8381P
	Function check				
	Warning/indicator lamps, illumination and interior lighting	\boxtimes	\otimes		
	Windshield wipers, windshield washer system	\mathbf{X}	\otimes		AP82.30-P-8252T
	Headlamp cleaning system	\mathbf{X}	\otimes		
	Check seat belts for damage and proper function		\otimes		AP91.40-P-9150P
	Check parking brake (function test only)		\otimes		AP42.00-P-4290BA
	Wheels, brakes				
	Check front brake pads for lining thickness (remove 1 front wheel)	X			AP42.10-P-4251BP
	Check brake pad thickness front/rear		\otimes		AP42.10-P-4251BP
	Check condition of brake discs front/rear		\otimes		AP42.10-P-4251BP
	Correct tire inflation pressure	\mathbf{X}	\otimes		
	Inspect tires for damage and condition	X	\otimes		AP40.10-P-4051Z
	Measure tread depth, enter in mm:		\otimes		AP40.10-P-4051Z
	LF RF LR RR outside				

completed	i ⊠	A-Service	• □ ↓	O B-Service ↓	Not O.I ↓	κ.
		Underside of vehicle Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		8		AP00.20-P-0053BA
		Check condition of front axle ball joints and rubber boots		\otimes		AP33.20-P-3353BP
		Check condition of steering's mechanical components and rubber boots		\otimes		AP46.00-P-4653F
		Engine compartment				
		 Leakage - Major components Check for chafe marks, line routing, damaged components In the event of leakage, determine cause and perform repair via separate work order 		8		AP00.20-P-0053BA
		Check condition of poly-V-belt		\otimes		AP13.22-P-1351Z
		Check catch, safety catch and hinges of engine hood for proper operation. i Replace components with even the slightest malfunction.	X	\otimes		
		Engine oil and filter change	X	\otimes		AP18.00-P-0101AE
		Check and correct fluid level I If there is a loss of fluid, determine caus and perform repair via separate work or				
		Engine cooling system, antifreeze and corrosion protection	X	\otimes		AP20.00-P-2010Z
		Brake system	X	\otimes		AP42.10-P-4210Z
		Power steering		\otimes		AP46.00-P-4611P
		Windshield washer	X	\otimes		AP82.35-P-8210P
		Battery, check and correct fluid level; check battery condition using "Midtronics MCR 717" tester	X	8		AP54.10-U-5453A

		Additional Work			
completed		Perform:	Yes ⊥	Not O.I	Κ.
	•	Once at first service at 10,000 mi or 1 year:	•	•	
r≆ AP		Parking brake - Adjust cable slack			AP42.20-P-4262P
		At approx. every 50,000 mi or 4 years:			
IF AP		Check condition of driveshafts flex discs			AP41.10-P-4152Z
		At approx. every 60,000 mi or 4 years:			
IF AP		Replace air cleaner filter element			
		At approx. every 60,000 mi or 5 years:			
IF≆ AP		Replace fuel filter			AP47.20-P-0780PV
IF AP		Replace activated charcoal filter			AP83.00-P-8382P
		At approx. every 150,000 mi or 15 years:			
r≆ AP		Replace coolant (water/anticorrosion/antifreeze)			AP20.00-P-2080A
		Replace spark plugs			
r≆ AP		At approx. every 100,000 mi or 5 years:			AP15.10-P-1580A
		Every 2 years:			
IF≆ AP		Replace brake fluid			AP42.00-P-4280BP
r≈ AP		Check body for paint damage by service Advisor			AP98.00-P-9850BA
j≆ AP		Check chassis and supporting body parts for damage and corrision by Service Advisor			AP00.20-P-0090BA
		Every 5 years:			
i≉ AP		Tilt/sliding roof: clean sliding rails and sliders			AP77.20-P-7731A

completed	i ⊠	Perform:	Yes ↓	Not O.K. ↓
		Vehicle over 150,000 mi:		
		Check if all fluid levels and changes are updated		
i≉ AP		Transmission		
if AP		Rear axle		
I≉ AP		Front axle (if applicable)		
i≉ AP		Transfer case (if applicable)		
		Check if air, fuel, ventilation filters are updated		
IF≆ AP		Engine air filter		
if Ap		Fuel filter		
I≉ AP		Combination / dust filter (if applicable)		
r≆ AP		Activated charcoal filter (if applicable)		
		Check integrity of engine, mechanical components		
i≉ AP		Perform compression test (hot and cold)		BE01.00-Z-9999AZ
IF≆ AP		Perform leak down test (hot and cold)		AP00.20-P-0053BA
IF≆ AP		Check spark plugs		
i≉ AP		Exhaust system hangers and leaks		
		Check damaged / worn drivetrain parts		
r≆ AP		Front wheel bearings play		
if AP		Rear wheel bearings play		
IF≆ AP		Axles joints play		
r≆ AP		Flexible discs		
IF AP		Tie rod and drag link joints		