

AP00.20-U-0001J

SERVICE SHEET for Flexible Service System (FSS)

6.12.99

MODEL 215

Passenger Cars Model Year 2003

USA/CANADA:

System is also known as "Active Service System (ASSYST)" in the Workshop Information System (WIS)

Model 215



| Cus | tomer: | - | Repair order number: | | | | | |
|---|---|--|---|--------------------------------|--|--|--|--|
| Confirm work has been performed by signing below | | | Type of service last performed On new vehicles start with B | | | | | |
| Technician: | | | В | A | | | | |
| | | Determine need for service: | | Τ' | | | | |
| | Please define type of | service to be performed here: | | | | | | |
| | Current | odometer reading: | | | | | | |
| | B-Service last p (Enter 0 if B-Service is | erformed at mi/km: performed for first time) | | | | | | |
| | Difference | in mi/km: | | | | | | |
| | | Difference < 14,000 mi 22,000 km A-Service | Difference ≥ 14,000 mi 22 000 km B-Service | | | | | |
| work" needed, if any: (check if applicable) | | 50,000 mi/80,000 km or 4 years | every: | 2 years | | | | |
| | | 60,000 mi/96,000 km or 4 years | | 3 years | | | | |
| at approx. | every: | 60,000 mi/96,000 km or 5 years | | Spark plugs | | | | |
| | | 150,000mi/250,000km or 15 years | | | | | | |
| Determ If the di | | | niles/22 000 km (as determined | from Service Booklet or dealer | | | | |

If the distance driven since the last "B- Service" is **greater** (≥) than 14,000 miles/22 000 km (as determined from Service Booklet or dealer records), a "B-Service" should be performed.

Additional flat rates apply for procedures marked with $\maltese P$.

| completed | IX L | A-Service | | O B-Service | Not O.K. | |
|-----------|---------|---|---------------------------|-------------|---------------|------------------|
| | ¥ | Vehicle passenger compartment | ¥ | • | ₩ . | |
| | | | | | | |
| | | Function check | | | | |
| | | Warning/indicator lamps, illumination and interior lighting | \boxtimes | \otimes | | |
| | | Windshield wipers, windshield washer system | \boxtimes | \otimes | | AP82.35-P-8252BA |
| | | Headlamp cleaning system | \boxtimes | \otimes | | |
| | | Check seat belts for damage and proper function | | \otimes | | AP91.40-P-9150M |
| | | Reset FSS counter in instrument cluster | \boxtimes | \otimes | | |
| | | Wheels, brakes | | | | |
| | | Check front brake pads for lining thickness (remove 1 front wheel at "A" service) | \boxtimes | | | AP42.10-P-4251I |
| | | Check brake pad thickness (front and rear) | | \otimes | | AP42.10-P-4251I |
| | | Check condition of brake discs front and rear | | \otimes | | AP42.10-P-4251I |
| | | Inspect tires for damage and condition | \boxtimes | \otimes | | AP40.10-P-4051Z |
| | | Measure tread depth, enter in mm: | | \otimes | | AP40.10-P-4051Z |
| | | LF RF LR RR | | | | |
| | | outside | | | | |
| | | middle | | | | |
| | | inside | | | | |
| | | Correct tire inflation pressure | \boxtimes | \otimes | | |
| | | Vehicle under body | | | | |
| completed | I⊠ ↓ | A-Service | $_{\downarrow}^{\square}$ | ○ B-Service | Not O.K. ↓ | |
| | | Visual check for Leakage - Major components Chafe marks, line routing, components. In the event of leakage, determine cause and perform repair via separate work order. | | ⊗ | | AP00.20-P-0053BA |
| | | Check condition of front axle ball joints and rubber boots | | \otimes | | AP33.20-P-3353BA |
| | | Check condition of steering's mechanical components and rubber boots | | \otimes | | AP46.00-P-4653F |
| | | Check tightening torque of power steering damper hydraulic line fittings. NOTE: Applies to chassis end number: 000652 to 007954 Review document: P-SC-2000090001 | \boxtimes | ⊗ | | AP46.20-U-4654A |

| | | Engine compartment | | | | | |
|-------------|-----|--|-------------|-----------|---|-----------|------------------|
| | | Visually check Leakage - Major components Chafe marks, line routing, components. In the event of leakage, determine cause and perform repair via separate work order. | | 8 | | | AP00.20-P-0053BA |
| | | Engine oil and filter change Engine 113 | \boxtimes | \otimes | | | AP18.00-P-0101AF |
| | | Engine 275 | | | | | |
| | | Check and correct fluid level | | | | | |
| | | Brake system | \boxtimes | \otimes | | | AP42.10-P-4210Z |
| | | Power steering | | \otimes | | / | AP46.00-P-4611BB |
| | | Active Body Control | | \otimes | | | AP32.50-P-3213I |
| | | Windshield washer | \boxtimes | \otimes | | | AP82.35-P-8210Z |
| | | Check catch, safety catch and hinges of engine hood for proper operation. Replace components with even the slightest malfunction. | \boxtimes | 8 | | | |
| | | Trunk | | | | | |
| | | Correct tire inflation pressure in spare tire | \boxtimes | \otimes | | | |
| | | If so equipped: Battery, wet cell Check acid level, replenish | \boxtimes | 8 | | | AP54.10-P-5410A |
| | | Additionally, check battery condition using "Midtronics MCR 717" Tester | \boxtimes | \otimes | | | SI54.10-P-0003A |
| | | If so equipped: Battery, AGM/VRLA, with black housing Check battery condition using "Midtronics MCR 717" Tester | \boxtimes | 8 | | | SI54.10-P-0003A |
| | | Additional work | | | | | |
| complete | d 🗵 | Perform: | yes | | N | ot O.K. | |
| | 1 | At approx. every 50,000 mi/96,000 km or 4 years: | ↓ | | | 1 | |
| ₽ AP | | Check condition of driveshaft flex discs | | | | | AP41.10-P-4152Z |
| | | At approx. every 60,000 mi/96,000 km or 4 years: | | | | | |
| ₩AP | | Replace air cleaner filter element | | | | | |
| | | | | | | | |

| | At approx. every 60,000 mi/96,000 km or 5 years: | | |
|-------------|---|---|------------------|
| | Check condition of poly-V-belt | | AP13.22-P-1351Z |
| FAP | Replace fuel filter Engine 113 | | AP47.20-P-0780DC |
| | Engine 275 | | |
| ₩AP | Replace activated charcoal filter | | AP83.00-P-8382M |
| | Every 2 years | * | |
| | Replace dust filter | | AP83.00-P-8381MA |
| ₩AP | Replace brake fluid | | AP42.00-P-4280BA |
| F AP | Check body for paint damage by Service Advisor | | AP98.00-P-9850BA |
| ₩AP | Check chassis and supporting body parts for damage and corrosion by Service Advisor | | AP00.20-P-0090BA |
| | Every 3 years | | |
| P AP | Replace coolant | | AP20.00-P-2080DA |
| ⊯ AP | Sliding/pop-up roof: clean sliding rails and sliders | | AP77.20-P-7731A |
| | At approx. 150,000 mi/250,000 km or 15 years | | |
| ₩AP | Replace coolant | | AP20.00-P-2080DA |
| | Replace spark plugs | | |
| ⊯ AP | At approx. every 60,000 mi/96,000 km or 5 years Engine 275 | | |
| № AP | At approx. every 100,000 mi/160,000 km or 5 years Engine 113 | | AP15.10-P-1580AB |