

AP00.20-U-1208T SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 5.10.04

MODEL 219

except AMG models

## Passenger cars Model Year 2006

Model 219

Customer:		Repair order numb	Repair order number:		
First visit	rst visit at 1,000 - 3,000 miles		YES NO		
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO		
Tire Inspection Inspect tires for damage and correct tire (staggered and non-staggered width wheel setup)		Tires inspected	YES NO		
Current mileage reading: Additional notes:			r:		
Service work to be performed as advised by service advisor:  Completion date: Confirm work has been performed by signing below:			rk has been performed by signing		

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
1.	2		Not OK ↓	
· ·		Engine compartment	•	
	0	Leakage - Major components Check for chafe marks, line routing, damaged components  i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053TX
	0	Check condition of poly-V-belt		AP13.22-P-1351TX
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851TX
	0	Check auxiliary battery condition using "Midtronics MCR 717" Tester		AP54.10-U-5453A
		Check fluid level, correct as required  i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Brake system		AP42.10-P-4210TX
	0	Power steering		AP46.00-P-4611TX
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210TX
		Interior		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042TX
	0	Function test  Chack parking brake (function test only)	П	AP42.00-P-4290TX
	0	Check parking brake (function test only)  Horn, warning/indicator lamps, illumination and interior lighting		AF42.00-F-42301A
	0	Audible warning system		AP54.30-P-5450TX
	0	Windshield wipers, windshield washer system		AP82.30-P-8252TX
	0	Headlamp cleaning system		
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150TX
	0	Check hydraulic unit of Sensotronic Brake Control (SBC)		AP42.50-P-4259TX
Wheels, b		Wheels, brakes		
·	0	Remove and install wheels		AP40.10-P-4050TX
		Check front brake pads for lining thickness (remove one front wheel)		AP42.10-P-4251TX
	0	Check front/rear brake pads for lining thickness		AP42.10-P-4251TX
	0	Check condition/thickness of front/rear brake discs		AP42.10-P-4251TX

<b>1</b> ↓	<b>2</b> ↓		Not OK ↓	
	Ō	Inspect tires for damage and splits, measu-		AP40.10-P-4051TX
		re tread depth, enter in mm:  LF RF LR RR		
		outside		
		center inside		
	0	Correct tire inflation pressure		
	3	Underside of vehicle		
	0	Leakage - Major components Check for chafe marks, line routing, dama-		AP00.20-P-0053TX
		ged components		
		i In the event of leakage, determine cause and perform repair via separate work or-		
		der		
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353TX
	0	Inspect condition of flexible discs		AP41.10-P-4152TX
	0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653TX
	Š	Trunk		
	0	Check main battery condition using "Mid- tronics MCR 717" Tester		AP54.10-U-5453A
	0	Correct inflation pressure in spare tire		
	0	Check trunk lighting		
	3)	Vehicle front/rear		
	0	Check wiper blade condition		AP82.30-P-8253G
0		Check and correct headlamp setting		AP82.10-P-8260TX
Completed ⊠ ↓			Not OK ↓	
US Service 3		every 13,000 mi or 1 year:		
		Engine compartment		
		Engine - oil and filter change		AP18.00-P-0101AF
US Service 4	_	every 2 years:		
	Ш	Check bodywork for paint work damage by service advisor	Ц	AP98.00-P-9850TX
		Engine compartment		
		Replace brake fluid Check preload pressure of pressure reservoir		AP42.00-P-4281TX
		Underside of vehicle		
		Chassis and load-bearing body components: Check for damage and corrosion by service advisor		AP00.20-P-0090TX

Completed ⊠	1		Not OK		
↓			<b>↓</b>		
US Service 5	every 26,000 mi or 2 years:				
	Engine compartment				
				AP83.00-P-8384TX	
US Service 6 & 7	not applicable				
US Service 8	every 52,000 mi or 4 years:				
	Engine compartment				
	Replace engine air-cleaner insert			AP09.10-P-0980TX	
US Service 9	every 5 years:				
	Passenger compartment				
	Tilting/sliding roof: Clean slide rail and sl de block	i-		AP77.20-P-7731TX	
US Service 10	not applicable				
US Service 11	every 65,000 mi or 5 years:				
	Underside of vehicle				
	Replace fuel filter			AP47.20-P-0780TX	
US Service 12	every 91,000 mi or 5 years:				
	Engine compartment				
	Replace spark plugs			AP15.10-P-1580TY	
US Service 13	every 143,000 mi or 15 years:				
	Engine compartment				
	Replace coolant			AP20.00-P-2080TX	
US Service 14 - 19	not applicable				
US Service 20	once at 39,000 mi:				
	Underside of vehicle				
	Automatic transmission - oil and filter change			AP27.00-P-2702W	
Completed ⊠	Perfor	m: Yes	Not OK		
↓		↓	<u></u>		
	Vehicle over 143,000 mi:				
	Check if all fluid levels and changes are u dated	p-			
i≆ AP □	Transmission				
F AP □	Rear axle				
	Check if air, fuel, ventilation filters are u dated	0-			
i≆ AP □	Engine air filter				
i≆ AP □	Fuel filter				
<b>⊯</b> AP □	Combination filter				
	Check damaged / worn drivetrain parts				
<b>⊯</b> AP □	Front wheel bearing play				
<b>⊯</b> AP □	Rear wheel bearing play				
<b>⊯</b> AP □	Axle joint play				
<b>⊯</b> AP □	Flexible discs				
F AP □	Tie rod and drag link joints				

	Completed ⊠		Perform:	Yes	Not OK	
	<b>1</b>			<b>↓</b>	<b>↓</b>	
		Check damaged / worn drivetrain parts				
₩ŶΑP		Front wheel bearing play				
₩ŶΑP		Rear wheel bearing play				
₩ŶΑP		Axle joint play				
₩ŶΑP		Flexible discs				
₩ÃΡ		Tie rod and drag link joints				