

AP00.20-U-1208TC SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 25.4.07

MODEL 219

except AMG models

Passenger cars Model Year 2008



Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading:			:	
Service work to be performed as advised by Completion date: Confirm work has been performed by signing below:				

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service	first at 13,000 mi or 1 year		after first every 26,000 mi or 2 years		
1	US Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years		
1	2 ↓		Not OK ↓		
		Engine compartment	·		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053TX	
	0	Check condition of poly-V-belt			
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851TX	
		Check fluid level, correct as required illf there is a loss of fluid, determine cause and perform repair via separate work order			
	0	Brake system		AP42.10-P-4210TX	
	0	Power steering		AP46.00-P-4611TX	
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210TX	
		Interior			
	0	Reset service indicator in instrument cluster		AP00.20-P-0042TX	
		Function test			
	0	Check parking brake (function test only)			
	0	Horn			
	0	Warning/indicator lamps, illumination and interior lighting		AP54.30-P-5452C	
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252TX	
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150TX	
		Wheels, brakes			
	. 0	Inspect tires for damage and splits, measure tread depth, enter in mm: LF RF LR RR outside		AP40.10-P-4051TX	
	0	Check front/rear brake pads for lining thickness		AP42.10-P-4253A	
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR bar/psi:			

US Service	US Serv			Not OK	
1 		2 ↓		↓	
· ·		·	Underside of vehicle	•	
} T	Ŧ	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053TX
		0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353TX
		0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152TX
		0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653TX
ide)	Vehicle front/rear		
		0	Check wiper blade condition		AP82.30-P-8253G
		0	Check and correct headlamp setting		AP82.10-P-8260TX
		Í	Trunk		
		0	Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		
		0	Check trunk lighting		
		0	Correct inflation pressure in spare tire and enter in bar or psi. bar/psi:		
Co	mpleted	× ↓		Not OK ↓	
US Sei	rvice 3		every 13,000 mi or 1 year:		
			Engine compartment		
			Engine - oil and filter change		AP18.00-P-0101TX
US Sei	rvice 4		every 2 years:		
			Check bodywork for paint work damage by service advisor		AP98.00-P-9850TX
			Engine compartment		
			Replace brake fluid		AP42.00-P-4280T
			Underside of vehicle		
			Chassis and load-bearing body components: Check for damage and corrosion by service advisor		AP00.20-P-0090TX
US Sei	rvice 5		not applicable		
US Sei	rvice 6		every 26,000 mi or 2 years:		
			Engine compartment		
			Replace combination filter		AP83.00-P-8384TX
US Sei	rvice 7		not applicable		

Completed 🗵			Not OK	
<u> </u>				
US Service 8	every 52,000 mi or 4 years:			
	Engine compartment			
<u>⊔</u>	Replace engine air-cleaner insert			AP09.10-P-0980TX
US Service 9	every 5 years:			
	Passenger compartment			A D 77 20 D 7724TV
	Tilting/sliding roof: Clean slide rail and slide block			AP77.20-P-7731TX
US Service 10	not applicable			
US Service 11	every 143,000 mi or 15 years:			
	Passenger compartment			
	Replace fuel filter			AP47.20-P-0780TX
US Service 12	every 91,000 mi or 5 years:			
Engine 273	Engine compartment			
<u></u>	Replace spark plugs			AP15.10-P-1580TX
US Service 13	every 143,000 mi or 15 years:			
	Engine compartment			4 DOG 60 D 3000TV
□ □	Replace coolant			AP20.00-P-2080TX
US Service 14 - 19	not applicable			
US Service 20	once at 39,000 mi:			
	Underside of vehicle			A DOZ 00 D 2702\A/
	Automatic transmission - oil and filter change			AP27.00-P-2702W
Completed ⊠	Perform:	Yes	Not OK	
↓		↓	<u></u>	
	Vehicle over 143,000 mi:			
	Check if all fluid levels and changes are up- dated			
F AP □	Transmission			
F AP □	Rear axle			
	Check if air, fuel, ventilation filters are updated			
 ⊯AP □	Engine air filter			
 ⊯AP □	Fuel filter			
	Combination filter			
_	Check integrity of engine, mechanical co-			
	monents			
I AP □	Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
⊯ AP □	Perform leak down test (hot and cold)			AP00.20-P-0053TX
⊯ AP □	Check spark plugs			
⊯ AP □	Exhaust system hangers and leaks			
	Check damaged / worn drivetrain parts			
⊯ AP □	Front wheel bearing play			
⊯AP □	Rear wheel bearing play			
— I≆*AP □	Axle joint play			
— ⊯AP □	Driveshaft flexible discs			
— I≆AP □	Tie rod and drag link joints			