

AP00.20-U-1208RAC SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 251

diesel models only

Light Truck Model Year 2008

USA

Customer:		Repair order number:	
First visit	at 1,000 - 3,000 miles	Performed	YES NO
Tire Rotation (non-staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO
Tire Inspection (staggered and non-staggered width wheel set up)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO
Current mileage reading:		Oil grade/viscosity:	
Additional notes:			
Service work to be performed as service advisor:	s advised by Completion date:	Confirm work below:	has been performed by signing

Model 251

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2 Perform each service as described.

US Service 1		first at 10,000 mi or 1 year;	after first every 20,000 mi or 2 years	
Ļ	US Service 2 ↓	first at 20,000 mi or 2 years;	after first every 20,000 mi or 2 years Not OK ↓	
	Ð	Interior		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042RT
_	-	Function test	_	
	0	Horn		
	0	Warning/indicator lamps, illumination and interior lighting		AP54.30-P-5452C
	0	Windshield wipers, windshield washer sy- stem, headlamp cleaning system		AP82.30-P-8252RT
	0	Check seat belts and buckles for signs of ex- ternal damage and proper function		AP91.40-P-9150RT
	0	Battery, check battery condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here.		
	0	Check parking brake (function test only)		
		Wheels, brakes	_	
	0	Inspect tires for damage and splits, measu- re tread depth, record in mm: LF RF LR RR outside		AP40.10-P-4051RT
	0	Check front/rear brake pads for lining thickness		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR bar/psi:		
		Underside of vehicle		
	0	Leakage - Major components Check for chafe marks, line routing, dama- ged components i In the event of leakage, determine cau- se and perform repair via separate work or- der		AP00.20-P-0053RT
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353RT
	0	Check rear axle ball joints for play, check rubber boots		AP35.20-P-3555RT
	0	Inspect play of tie rod and and drag link joints, inspect rubber boots		AP46.00-P-4653RT
toe		Vehicle front/rear		
	0	Check wiper blade condition		AP82.30-P-8253G
	0	Check and correct headlamp setting		AP82.10-P-8260RT

	US Service 2		Not OK	
1 ↓	∠ ↓		Ļ	
		Engine compartment		
	0	Leakage - Major components Check for chafe marks, line routing, dama- ged components Îln the event of leakage, determine cau- se and perform repair via separate work or- der		AP00.20-P-0053RT
	0	Check catch, safety catch and hinges on en- gine hood for proper operation.		AP88.40-P-8851RT
	0	Check condition of poly-V-belt		
		Check fluid level, correct as required ilf there is a loss of fluid, determine cau- se and perform repair via separate work or- der		
	0	Brake system		AP42.10-P-4210RT
	0	Power steering		AP46.00-P-4611RT
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210RT
	0	Drain fuel filter		AP47.20-P-0794A
	0	Clean water drain in air/water duct		AP83.10-P-8339M
		Additional Work		
Co	ompleted ⊠ ↓		Not OK ↓	
US Ser	rvice 3	every 10,000 mi or 1 year:		
		Engine compartment		
		Engine - oil and filter change		AP18.00-P-0101TQ
US Ser	rvice 4	every 2 years:		
		Check bodywork for paint work damage by service advisor		AP98.00-P-9850RT
		Underside of vehicle Chassis and load-bearing body compo- nents: Check for damage and corrosion by service advisor		AP00.20-P-0090RT
		Engine compartment		
		Replace brake fluid		AP42.00-P-4280RT
US Ser	rvice 5	every 30,000 mi or 2 years:		
		Passenger compartment		
		Replace combination filter		AP83.00-P-8384RT
US Servic	e 6 and 7	not applicable		
US Ser	rvice 8	every 40,000 mi or 4 years: Engine compartment		
		Replace engine air-cleaner insert		AP09.10-P-0980RTD
US Ser	rvice 9	not applicable		
US Serv	vice 10	every 3 years: Passenger compartment		
		Panorama sliding roof: Clean and lubricate guide mechanism		AP77.20-P-7732RT

Com	pleted 🗵		Not OK	
	¥		Ļ	
US Servi	ce 11	every 20,000 mi or 2 years: Engine compartment		
		Replace fuel filter	AP47.20-P-0780RT	ΓD
US Servi	ce 13	every 150,000 mi or 15 years:		
		Engine compartment		
		Replace coolant	AP20.00-P-2080RT	ΓD
US Service	e 14-19	not applicable		
US Service 20		once at 40,000 mi:		
		Underside of vehicle		
		Automatic transmission - oil and filter change	AP27.00-P-2702W	/
		Vehicle over 150,000 mi:		
		Check if all fluid levels and changes are up- dated		
AP		Transmission		
₩ AP		Rear axle		
AP		Front axle		
AP		Transfer case		
		Check if air, fuel, ventilation filters are up- dated		
μarap		Engine air filter		
₩ AP		Fuel filter		
₩ AP		Combination filter		
		Check integrity of engine, mechanical co- monents		
₩AP		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ		
₩ ° AP		Perform leak down test (hot and cold)	AP00.20-P-0053RT	Г
₩ ° AP		Check spark plugs		
₩ ° AP		Exhaust system hangers and leaks		
		Check damaged / worn drivetrain parts		
₩°́АР		Front wheel bearing play		
₩ ° AP		Rear wheel bearing play		
₩ AP		Axles joint play		
₩ AP		Driveshaft flexible discs		
AP		Tie rod and drag link joints		